

# Nissen by Markal Jumbo Feltip Paint Marker: White, Yellow, Black, Red

## Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 11/2/2017 Version: 1.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : Nissen by Markal Jumbo Feltip Paint Marker: White, Yellow, Black, Red

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Use of the substance/mixture : Marking.

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

North America:

LA-CO Industries, Inc.  
1201 Pratt Boulevard  
Elk Grove Village, IL. 60007-5746  
Phone: (847) 956-7600  
Fax: (847) 956-9885  
E-mail: customer\_service@laco.com



Europe:

LA-CO Industries Europe S.A.S.  
Parc Industriel de la Plaine de  
l'Ain - Allée des Combes.  
01150.BLYES.France.  
Phone: +33 (0)4 74 46 23 23  
Fax: +33 (0)4 74 46 23 29  
E-mail: info@eu.laco.com  
Web: http://www.markal.com

#### 1.4. Emergency telephone number

Emergency number : 24-hour emergency: CHEMTREC- U.S. : 1-800-424-9300 International: +1-703-527-3887

EU Member State	Officieel adviesorgaan	Adres	Noodnummer
AUSTRIA	Vergiftungsinformationszentrale (Poisons Information Centre)	Allgemeines Krankenhaus Waehringer Geurtel 18-20 1090 Wien	+43 1 406 43 43
BELARUS	The Belarus Republican Poisons Centre	Kizhevatova str. 58 Minsk 220115	+375 (0)17 201 9158
BELGIUM	Centre Anti-Poisons/Antigifocentrum c/o Hôpital Central de la Base - Reine Astrid	Rue Bruyn 1 B -1120 Bruxelles/Brussel	+32 70 245 245
BULGARIA	Национален токсикологичен информационен център National Clinical Toxicology Centre, Emergency Medical Institute "Pirogov"	21 Totleben Boulevard 1606 SOFIA	+359 2 9154 409
CROATIA	Poisons Control Centre Institute of Medical Research & Occupational Health	Ksaverska Cesta 2 P.O. Box 291 HR-10000 Zagreb	+385 1 234 8342
CZECH REPUBLIC	Toxikologické informační středisko Clinic For Occupational Medicine, 1st Medical Faculty, Charles University	Na Bojišti 1 120 00 Praha 2	+42 2 2491 9293 +42 2 2491 5402
DENMARK	Gifflinjen Bispebjerg Hospital	Bispebjerg Bakke 23, 60, 1 DK-2400 København NV	+45 82 12 12 12 +45 35 31 55 55
ESTONIA	Mürgistusteabekeskus	Gonsiori 29 15027 Tallinn	+372 626 93 90
FINLAND	Myrkytystietokeskus	P.O.B 340 (Haartmaninkatu 4) HUS SF - 00029 Helsinki	+358 9 471 977
FRANCE	ORFILA		+33 1 45 42 59 59

# Nissen by Markal Jumbo Feltip Paint Marker: White, Yellow, Black, Red

## Safety Data Sheet

according to Regulation (EU) 2015/830

GERMANY	Berliner Betrieb für Zentrale Gesundheitliche Aufgaben	Oranienburger Strasse 285 13437 Berlin	+49 30 19240
GERMANY	Informations und Beratungszentrum für Vergiftungsfälle	Kirrberger Straße, Gebäude 9 D-66421 Homburg/Saar	+49 6841 19240
GERMANY	Beratungstelle bei Vergiftungen, Klinische Toxikologie und Beratungsstelle bei Vergiftungen	Langenbeckstrasse 1 55131 Mainz	+49 6131 19240
GREECE	Poisons Information Centre	11527 Athens	+30 10 779 3777
HUNGARY	Országos Kémiai Biztonsági Intézet (National Institute of Chemical Safety) Egészségügyi Toxikológiai Tájékoztató Szolgálat (Health Toxicological Information Service)	1437 Budapest PO Box 839 1097 Budapest, Nagyvárad tér 2	+36 80 20 11 99
ICELAND	Eitrunarmiðstöðin	Eitrunarmiðstöðin 108 Reykjavik	+354 543 22 22
IRELAND	National Poisons Information Centre	Beaumont Hospital PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2166
LATVIA	Valsts Toksikoloģijas centra Saindēšanās un zāļu informācijas centrs	2 Hipocrate Street LV 1038 Riga	+371 67 04 24 73
LITHUANIA	Apsinuodijimų kontrolės ir informacijos biuras	Siltnamiu 29 2043 Vilnius	+370 5 236 20 52/+370 687 53 378
MALTA	Medicines & Poisons Info Office	Mater Dei Hospital, Msida MSD 2090 Malta	25450000
NETHERLANDS	Nationaal Vergiftigingen Informatie Centrum National Institute for Public Health and the Environment, NB this service is only available to health professionals	Huispostnummer B.00.118, PO Box 85500 3508 GA Utrecht	+31 30 274 88 88
PORTUGAL	Centro de Informação Antivenenos Instituto Nacional de Emergência Médica (INEM)	Rua Almirante Barroso, 36 1000-013 Lisboa	808 250 143 (for use only in Portugal), +351 21 330 3284
ROMANIA	Biroul pentru Regulamentul Sanitar International si Informare Toxicologica	Str. Dr. Leonte Anastasievici Nr.1-3, Sector 5 50463 Bucuresti	+40 21 318 36 06
SLOVAKIA	Národné toxikologické informačné centrum University Hospital Bratislava	Limbová 5 833 05 Bratislava	+421 2 54 77 4 166
SPAIN	Servicio de Información Toxicológica Instituto Nacional de Toxicología, Departamento de Madrid	Calle Luis Cabrera 9 E-28002 Madrid	+34 91 562 04 20
SWEDEN	Giftinformationscentralen Swedish Poisons Information Centre, Karolinska Hospital	Box 60 500 SE-171 76 Stockholm	+46 8 33 12 31 (International) 112 (National)
SWITZERLAND	Centre Suisse d'Information Toxicologique	Freiestrasse 16 Postfach CH-8028 Zurich	+41 44 251 51 51 (International) 145 (National)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3	H226
Acute toxicity (inhalation:dust,mist) Category 4	H332
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Carcinogenicity, Category 2	H351
Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation	H335
Specific target organ toxicity — Repeated exposure, Category 2	H373

Full text of H statements : see section 16

#### Adverse physicochemical, human health and environmental effects

No additional information available

# Nissen by Markal Jumbo Feltip Paint Marker: White, Yellow, Black, Red

## Safety Data Sheet

according to Regulation (EU) 2015/830

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

GHS08

Signal word (CLP) :

Warning

Hazardous ingredients :

Ethylbenzene; Titanium dioxide; Xylene; Carbon black

Hazard statements (CLP) :

H226 - Flammable liquid and vapour.  
H315 - Causes skin irritation.  
H319 - Causes serious eye irritation.  
H332 - Harmful if inhaled.  
H335 - May cause respiratory irritation.  
H351 - Suspected of causing cancer.  
H373 - May cause damage to organs through prolonged or repeated exposure.

Precautionary statements (CLP) :

P201 - Obtain special instructions before use.  
P202 - Do not handle until all safety precautions have been read and understood.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 - Keep container tightly closed.  
P240 - Ground and bond container and receiving equipment.  
P241 - Use explosion-proof equipment.  
P260 - Do not breathe dust/fume/gas/mist/vapours/spray.  
P264 - Wash hands, forearms and face thoroughly after handling.  
P271 - Use only outdoors or in a well-ventilated area.  
P280 - Wear protective gloves/protective clothing/eye protection/face protection.  
P302+P352 - IF ON SKIN: Wash with plenty of water  
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .  
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P308+P313 - IF exposed or concerned: Get medical advice/attention.  
P312 - Call a POISON CENTRE or doctor if you feel unwell.  
P321 - Specific treatment (see supplemental first aid instruction on this label)  
P332+P313 - If skin irritation occurs: Get medical advice/attention.  
P337+P313 - If eye irritation persists: Get medical advice/attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P370+P378 - In case of fire: Use media other than water to extinguish.  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
P403+P235 - Store in a well-ventilated place. Keep cool.  
P405 - Store locked up.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbon resin	(CAS-No.) 68131-77-1 (EC-No.) 614-301-5	51: Black 26: Red, White, Yellow	Not classified

# Nissen by Markal Jumbo Feltip Paint Marker: White, Yellow, Black, Red

## Safety Data Sheet

according to Regulation (EU) 2015/830

Xylene	(CAS-No.) 1330-20-7 (EC-No.) 215-535-7 (EC Index-No.) 601-022-00-9	49: White 42: Yellow 33: Red and Black	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
Titanium dioxide	(CAS-No.) 13463-67-7 (EC-No.) 236-675-5	24: White 17: Red and Yellow	Carc. 2, H351 (as dust)
Colorant		23: Red 14: Yellow	Not classified
Carbon black	(CAS-No.) 1333-86-4 (EC-No.) 215-609-9	15	Carc. 2, H351 (as dust)
Ethylbenzene	(CAS-No.) 100-41-4 (EC-No.) 202-849-4 (EC Index-No.) 601-023-00-4	1	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation:dust,mist), H332 Carc. 2, H351 STOT RE 2, H373 Asp. Tox. 1, H304

Full text of H-statements: see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- First-aid measures general : IF exposed or concerned: Get medical advice/attention.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
- First-aid measures after skin contact : Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects after inhalation : May cause respiratory irritation.
- Symptoms/effects after skin contact : Irritation.
- Symptoms/effects after eye contact : Eye irritation.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

#### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Flammable liquid and vapour.
- Explosion hazard : Flammable vapours heavier than air/can accumulate.
- Hazardous decomposition products in case of fire : Toxic fumes may be released.

#### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Emergency procedures : No open flames, no sparks, and no smoking. Do not breathe vapours. Avoid contact with skin, eyes and clothing.

##### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Avoid release to the environment.

# Nissen by Markal Jumbo Feltip Paint Marker: White, Yellow, Black, Red

## Safety Data Sheet

according to Regulation (EU) 2015/830

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.  
Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Do not handle until all safety precautions have been read and understood. Do not breathe vapours/spray. Use only outdoors or in a well-ventilated area. Do not get in eyes, on skin, or on clothing. Wear Nitrile rubber gloves, natural rubber gloves. Gloves must be replaced after each use and whenever signs of wear or perforation appear.  
Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed.  
Incompatible products : Strong oxidizers.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Ethylbenzene (100-41-4)		
EU	Local name	Ethylbenzene
EU	IOELV TWA (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup>
EU	IOELV TWA (ppm)	100 ppm
EU	IOELV STEL (mg/m <sup>3</sup> )	884 mg/m <sup>3</sup>
EU	IOELV STEL (ppm)	200 ppm
EU	Notes	Skin
Czech Republic	Local name	Ethylbenzen
Czech Republic	Expoziční limity (PEL) (mg/m <sup>3</sup> )	200 mg/m <sup>3</sup>
Czech Republic	Expoziční limity (PEL) (ppm)	50 ppm
Czech Republic	Expoziční limity (NPK-P) (mg/m <sup>3</sup> )	500 mg/m <sup>3</sup>
Czech Republic	Expoziční limity (NPK-P) (ppm)	120 ppm
Czech Republic	Remark (CZ)	D
Denmark	Local name	Ethylbenzen
Denmark	Grænseværdie (langvarig) (mg/m <sup>3</sup> )	217 mg/m <sup>3</sup>
Denmark	Grænseværdie (langvarig) (ppm)	50 ppm
Denmark	Grænseværdie (kortvarig) (mg/m <sup>3</sup> )	434 mg/m <sup>3</sup>
Denmark	Grænseværdie (kortvarig) (ppm)	100 ppm
Denmark	Anmærkninger (DK)	E (betyder, at stoffet har en EF-grænseværdi); K (betyder, at stoffet anses for at kunne være kræftfremkaldende)
Finland	Local name	Etylibentseeni
Finland	HTP-arvo (8h) (mg/m <sup>3</sup> )	220 mg/m <sup>3</sup>
Finland	HTP-arvo (8h) (ppm)	50 ppm
Finland	HTP-arvo (15 min)	880 mg/m <sup>3</sup>
Finland	HTP-arvo (15 min) (ppm)	200 ppm
France	Local name	Ethylbenzène
France	VME (mg/m <sup>3</sup> )	88.4 mg/m <sup>3</sup>
France	VME (ppm)	20 ppm
France	VLE (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup>

# Nissen by Markal Jumbo Feltip Paint Marker: White, Yellow, Black, Red

## Safety Data Sheet

according to Regulation (EU) 2015/830

Ethylbenzene (100-41-4)		
France	VLE (ppm)	100 ppm
France	Note (FR)	Peau
Germany	Local name	Ethylbenzol
Germany	TRGS 900 Occupational exposure limit value (mg/m <sup>3</sup> )	88 mg/m <sup>3</sup>
Germany	TRGS 900 Occupational exposure limit value (ppm)	20 ppm
Germany	Remark (TRGS 900)	DFG,H,Y,EU
Germany	TRGS 903 (BGW)	1 mg/l Ethylbenzol (Blut; Expositionsende bzw. Schichtende) 800 mg/l Mandelsäure + Phenylglyoxylsäure (Urin; Expositionsende bzw. Schichtende)
Hungary	Local name	ETILBENZOL
Hungary	AK-érték	442 mg/m <sup>3</sup>
Hungary	CK-érték	884 mg/m <sup>3</sup>
Hungary	Megjegyzések (HU)	b, i; l.
Italy	Local name	Etilbenzene
Italy	OEL TWA (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup>
Italy	OEL TWA (ppm)	100 ppm
Italy	OEL STEL (mg/m <sup>3</sup> )	884 mg/m <sup>3</sup>
Italy	OEL STEL (ppm)	200 ppm
Latvia	Local name	Etilbenzols
Latvia	OEL TWA (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup>
Latvia	OEL TWA (ppm)	100 ppm
Latvia	OEL STEL (mg/m <sup>3</sup> )	884 mg/m <sup>3</sup>
Latvia	OEL STEL (ppm)	200 ppm
Netherlands	Local name	Ethylbenzeen
Netherlands	Grenswaarde TGG 8H (mg/m <sup>3</sup> )	215 mg/m <sup>3</sup>
Netherlands	Grenswaarde TGG 15MIN (mg/m <sup>3</sup> )	430 mg/m <sup>3</sup>
Netherlands	Remark (MAC)	H (Huidopname) Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een Haanduiding. Bij deze stoffen moeten naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen.
Poland	Local name	Etylobenzen
Poland	NDS (mg/m <sup>3</sup> )	200 mg/m <sup>3</sup>
Poland	NDSch (mg/m <sup>3</sup> )	400 mg/m <sup>3</sup>
Portugal	Local name	Etilbenzeno
Portugal	OEL TWA (ppm)	20 ppm
Slovakia	Local name	Etylbenzén
Slovakia	NPHV (priemerná) (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup> (K)
Slovakia	NPHV (priemerná) (ppm)	100 ppm (K) 12 ppm (2 - a 4 -Etylfenol) 1600 ppm (Kyselina mandlová a kyselina fenyglyoxylová)
Slovakia	OEL STEL (mg/m <sup>3</sup> )	884 mg/m <sup>3</sup>
Slovakia	OEL STEL (ppm)	200 ppm
Slovenia	Local name	etilbenzen
Slovenia	OEL TWA (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup>
Slovenia	OEL TWA (ppm)	100 ppm
Slovenia	OEL STEL (mg/m <sup>3</sup> )	884 mg/m <sup>3</sup>
Slovenia	OEL STEL (ppm)	200 ppm

# Nissen by Markal Jumbo Feltip Paint Marker: White, Yellow, Black, Red

## Safety Data Sheet

according to Regulation (EU) 2015/830

<b>Ethylbenzene (100-41-4)</b>		
Spain	Local name	Etilbenceno
Spain	VLA-ED (mg/m <sup>3</sup> )	441 mg/m <sup>3</sup> via dérmica, VLB, VLI
Spain	VLA-ED (ppm)	100 ppm via dérmica, VLB, VLI 700 ppm I, S "(Suma del ácido mandélico y el ácido fenilgloxílico en orina; Final de la semana laboral 1)"
Spain	VLA-EC (mg/m <sup>3</sup> )	884 mg/m <sup>3</sup> via dérmica, VLB, VLI
Spain	VLA-EC (ppm)	200 ppm via dérmica, VLB, VLI
Sweden	Local name	Etylbensen
Sweden	nivågränsvärde (NVG) (mg/m <sup>3</sup> )	220 mg/m <sup>3</sup>
Sweden	nivågränsvärde (NVG) (ppm)	50 ppm
Sweden	kortidsvärde (KTV) (mg/m <sup>3</sup> )	884 mg/m <sup>3</sup>
Sweden	kortidsvärde (KTV) (ppm)	200 ppm
Norway	Local name	Etylbenzen
Norway	Grenseverdier (AN) (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup>
Norway	Grenseverdier (AN) (ppm)	5 ppm
Norway	Merknader (NO)	H (Kjemikalier som kan tas opp gjennom huden); K (Kjemikalier som skal betraktes som kreftfremkallende); E (EU har en veiledende grenseverdi for stoffet)
<b>Titanium dioxide (13463-67-7)</b>		
EU	Local name	Titanium dioxide
EU	Notes	(Ongoing)
Belgium	Remark (BE)	(dioxyde de)
Denmark	Local name	Titandioxid
Denmark	Grænseværdie (langvarig) (mg/m <sup>3</sup> )	6 mg/m <sup>3</sup> beregnet som Ti
Denmark	Grænseværdie (kortvarig) (mg/m <sup>3</sup> )	12 mg/m <sup>3</sup>
France	Local name	Titane (dioxyde de), en Ti
France	VME (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
France	Note (FR)	inhalable aerosol
Germany	TRGS 900 Occupational exposure limit value (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> E (mg/m <sup>3</sup> )
Ireland	OEL (8 hours ref) (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> total inhalable dust 4 mg/m <sup>3</sup> respirable dust
Latvia	Local name	Titānadioksīds
Latvia	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Portugal	Local name	Dióxido de titânio
Portugal	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Slovakia	Local name	Oxid titaničitý
Slovakia	NPHV (priemerná) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
Spain	Local name	Dióxido de titanio
Spain	VLA-ED (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Spain	Notes	inhalable aerosol
Sweden	Local name	Titandioxid
Sweden	nivågränsvärde (NVG) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
Sweden	Anmärkning (SE)	total dust, 1
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> inhalable aerosol 4 mg/m <sup>3</sup> respirable aerosol
Norway	Local name	Titandioksid
Norway	Grenseverdier (AN) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
Switzerland	Remark (CH)	(respirable aerosol)
<b>Xylene (1330-20-7)</b>		
EU	Local name	Xylene, mixed isomers, pure
EU	IOELV TWA (mg/m <sup>3</sup> )	221 mg/m <sup>3</sup>
EU	IOELV TWA (ppm)	50 ppm

# Nissen by Markal Jumbo Feltip Paint Marker: White, Yellow, Black, Red

## Safety Data Sheet

according to Regulation (EU) 2015/830

Xylene (1330-20-7)		
EU	IOELV STEL (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup>
EU	IOELV STEL (ppm)	100 ppm
EU	Notes	Skin
Austria	MAK (mg/m <sup>3</sup> )	221 mg/m <sup>3</sup> (H)
Austria	MAK (ppm)	50 ppm (H)
Austria	MAK Short time value (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup> max. 4x15 min./Schicht, (H)
Austria	MAK Short time value (ppm)	100 ppm max. 4x15 min./Schicht, (H)
Belgium	Limit value (mg/m <sup>3</sup> )	221 mg/m <sup>3</sup>
Belgium	Limit value (ppm)	50 ppm
Belgium	Short time value (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup>
Belgium	Short time value (ppm)	100 ppm
Belgium	Remark (BE)	D
Czech Republic	Local name	Xylen technická směs isomerů a všechny isomery
Czech Republic	Expoziční limity (PEL) (mg/m <sup>3</sup> )	200 mg/m <sup>3</sup>
Czech Republic	Expoziční limity (PEL) (ppm)	46 ppm
Czech Republic	Expoziční limity (NPK-P) (mg/m <sup>3</sup> )	400 mg/m <sup>3</sup>
Czech Republic	Expoziční limity (NPK-P) (ppm)	92 ppm
Czech Republic	Remark (CZ)	D,I
Denmark	Local name	Xylen (Dimethylbenzen), alle isomere
Denmark	Grænseværdie (langvarig) (mg/m <sup>3</sup> )	109 mg/m <sup>3</sup>
Denmark	Grænseværdie (langvarig) (ppm)	25 ppm
Denmark	Grænseværdie (kortvarig) (mg/m <sup>3</sup> )	218 mg/m <sup>3</sup>
Denmark	Grænseværdie (kortvarig) (ppm)	50 ppm
Denmark	Anmærkninger (DK)	H
Finland	Local name	Ksyleeni
Finland	HTP-arvo (8h) (mg/m <sup>3</sup> )	220 mg/m <sup>3</sup>
Finland	HTP-arvo (8h) (ppm)	50 ppm
Finland	HTP-arvo (15 min)	440 mg/m <sup>3</sup>
Finland	HTP-arvo (15 min) (ppm)	100 ppm
Finland	Huomautus (FI)	iho
France	Local name	Xylène, isomères mixtes, purs
France	VME (mg/m <sup>3</sup> )	221 mg/m <sup>3</sup>
France	VME (ppm)	50 ppm
France	VLE (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup>
France	VLE (ppm)	100 ppm
France	Note (FR)	Valeurs réglementaires contraignantes; risque de pénétration percutanée
Germany	Local name	Xylol (alle Isomeren)
Germany	TRGS 900 Occupational exposure limit value (mg/m <sup>3</sup> )	440 mg/m <sup>3</sup>
Germany	TRGS 900 Occupational exposure limit value (ppm)	100 ppm
Germany	Remark (TRGS 900)	H
Hungary	Local name	XILOL(ok)
Hungary	AK-érték	221 mg/m <sup>3</sup>
Hungary	CK-érték	442 mg/m <sup>3</sup>
Hungary	Megjegyzések (HU)	b; EU1
Ireland	OEL (8 hours ref) (mg/m <sup>3</sup> )	221 mg/m <sup>3</sup>
Ireland	OEL (8 hours ref) (ppm)	50 ppm
Ireland	OEL (15 min ref) (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup>
Ireland	OEL (15 min ref) (ppm)	100 ppm
Ireland	Notes (IE)	Sk, IOELV



# Nissen by Markal Jumbo Feltip Paint Marker: White, Yellow, Black, Red

## Safety Data Sheet

according to Regulation (EU) 2015/830

Xylene (1330-20-7)		
Italy	Local name	Xilene, isomeri misti, puro
Italy	OEL TWA (mg/m <sup>3</sup> )	221 mg/m <sup>3</sup>
Italy	OEL TWA (ppm)	50 ppm
Italy	OEL STEL (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup>
Italy	OEL STEL (ppm)	100 ppm
Latvia	Local name	Ksilols (o-,m-,p-ksilols, dimetilbenzols)
Latvia	OEL TWA (mg/m <sup>3</sup> )	221 mg/m <sup>3</sup>
Latvia	OEL TWA (ppm)	50 ppm
Latvia	OEL STEL (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup>
Latvia	OEL STEL (ppm)	100 ppm
Lithuania	IPRV (mg/m <sup>3</sup> )	200 mg/m <sup>3</sup>
Lithuania	IPRV (ppm)	50 ppm
Lithuania	TPRV (mg/m <sup>3</sup> )	450 mg/m <sup>3</sup>
Lithuania	TPRV (ppm)	100 ppm
Lithuania	Remark (LT)	O
Netherlands	Local name	Xyleen, o-, m-, p-isomeren
Netherlands	Grenswaarde TGG 8H (mg/m <sup>3</sup> )	210 mg/m <sup>3</sup>
Netherlands	Grenswaarde TGG 8H (ppm)	50 ppm
Netherlands	Grenswaarde TGG 15MIN (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup>
Netherlands	Remark (MAC)	(H)
Poland	Local name	Ksylen mieszanina izomerów: 1,2-; 1,3-; 1,4-
Poland	NDS (mg/m <sup>3</sup> )	100 mg/m <sup>3</sup>
Poland	NDSch (mg/m <sup>3</sup> )	350 mg/m <sup>3</sup>
Portugal	Local name	Xileno (isómeros )
Portugal	OEL TWA (ppm)	100 ppm
Portugal	OEL STEL (ppm)	150 ppm
Slovakia	Local name	Xylén, zmiešané izoméry
Slovakia	NPHV (priemerná) (mg/m <sup>3</sup> )	221 mg/m <sup>3</sup> (K)
Slovakia	NPHV (priemerná) (ppm)	50 ppm (K) 1.5 ppm (Xylén) 2000 ppm (Suma kyselín 2,3,4-metylhippurových)
Slovakia	OEL STEL (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup>
Slovakia	OEL STEL (ppm)	100 ppm
Slovakia	Upozornenie (SK)	K - znamená, že faktor môže byť ľahko absorbovaný kožou
Slovenia	Local name	ksilen (mešane izomere)
Slovenia	OEL TWA (mg/m <sup>3</sup> )	221 mg/m <sup>3</sup>
Slovenia	OEL TWA (ppm)	50 ppm
Slovenia	KTV factor SL	2
Spain	Local name	Xilenos
Spain	VLA-ED (mg/m <sup>3</sup> )	221 mg/m <sup>3</sup> vía dérmica,VLB,VLI
Spain	VLA-ED (ppm)	50 ppm vía dérmica,VLB,VLI 1.5 ppm (Ácidos metilhipúricos en orina; Final de la jornada laboral 2)
Spain	VLA-EC (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup> vía dérmica,VLB,VLI
Spain	VLA-EC (ppm)	100 ppm vía dérmica,VLB,VLI

# Nissen by Markal Jumbo Feltip Paint Marker: White, Yellow, Black, Red

## Safety Data Sheet

according to Regulation (EU) 2015/830

<b>Xylene (1330-20-7)</b>		
Spain	Notes	Vía dérmica (Indica que, en las exposiciones a esta sustancia, la aportación por la vía cutánea puede resultar significativa para el contenido corporal total si no se adoptan medidas para prevenir la absorción. En estas situaciones, es aconsejable la utilización del control biológico para poder cuantificar la cantidad global absorbida del contaminante), VLB® (Agente químico que tiene Valor Límite Biológico), VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo).
Spain		1 g/g creatinine Parámetro: Ácidos metilhipúricos - Medio: Orina - Momento de muestreo: Final de la jornada laboral
Sweden	Local name	Xylen
Sweden	nivågränsvärde (NVG) (mg/m <sup>3</sup> )	221 mg/m <sup>3</sup>
Sweden	nivågränsvärde (NVG) (ppm)	50 ppm
Sweden	kortidsvärde (KTV) (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup>
Sweden	kortidsvärde (KTV) (ppm)	100 ppm
Sweden	Anmärkning (SE)	(H)
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	220 mg/m <sup>3</sup> (Sk)
United Kingdom	WEL TWA (ppm)	50 ppm (Sk) 650 ppm (methyl hippuric acid/mol creatinine in urine, Post shift)
United Kingdom	WEL STEL (mg/m <sup>3</sup> )	441 mg/m <sup>3</sup> (Sk)
United Kingdom	WEL STEL (ppm)	100 ppm (Sk)
Norway	Local name	Xylen (alle isomere)
Norway	Grenseverdier (AN) (mg/m <sup>3</sup> )	108 mg/m <sup>3</sup>
Norway	Grenseverdier (AN) (ppm)	25 ppm
Norway	Merknader (NO)	H
Switzerland	VME (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
Switzerland	MAK (ppm)	100 ppm 1.5 ppm Methylhippur-(Tolur)-säure (urina; in caso di esposizione per molto tempo/fine dell'esposizione / del turno) 1.5 ppm xilolo (sangue; fine dell'esposizione / del turno)
Switzerland	KZGW (mg/m <sup>3</sup> )	870 mg/m <sup>3</sup> max. 4x30 min./turno
Switzerland	KZGW (ppm)	200 ppm max. 4x30 min./turno
Australia	TWA (mg/m <sup>3</sup> )	441 mg/m <sup>3</sup>
<b>Carbon black (1333-86-4)</b>		
Belgium	Limit value (mg/m <sup>3</sup> )	3.5 mg/m <sup>3</sup>
Denmark	Local name	Carbon black
Denmark	Grænseværdie (langvarig) (mg/m <sup>3</sup> )	3.5 mg/m <sup>3</sup>
Denmark	Anmærkninger (DK)	K
Finland	Local name	Nokimusta
Finland	HTP-arvo (8h) (mg/m <sup>3</sup> )	3.5 mg/m <sup>3</sup>
Finland	HTP-arvo (15 min)	7 mg/m <sup>3</sup>
France	Local name	Noir de carbone
France	VME (mg/m <sup>3</sup> )	3.5 mg/m <sup>3</sup>
France	Note (FR)	Valeurs recommandées/admises
Ireland	OEL (8 hours ref) (mg/m <sup>3</sup> )	3.5 mg/m <sup>3</sup>
Ireland	OEL (15 min ref) (mg/m <sup>3</sup> )	7 mg/m <sup>3</sup>
Portugal	Local name	Carbono, preto (Negro de fumo)
Portugal	OEL TWA (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup> I (Fração inalável)
Spain	Local name	Negro de humo
Spain	VLA-ED (mg/m <sup>3</sup> )	3.5 mg/m <sup>3</sup>

# Nissen by Markal Jumbo Feltip Paint Marker: White, Yellow, Black, Red

## Safety Data Sheet

according to Regulation (EU) 2015/830

Carbon black (1333-86-4)		
Sweden	Local name	Kimrök
Sweden	nivågränsvärde (NVG) (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup>
Sweden	Anmärkning (SE)	2 (Med totaldamm menas de partiklar (aerosoler) som fastnar på ett filter i den provtagare som beskrivs i Metodserien, Provtagning av totaldamm och respirabelt damm, Metod nr 1010, Arbetarskyddsstyrelsen, numera Arbetsmiljöverket. Filterdiametern är normalt 37 mm, men kan även vara 25 mm. Trots sitt namn provtas inte den totala mängden luftburna partiklar med denna metod)
United Kingdom	Local name	Carbon black
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	3.5 mg/m <sup>3</sup>
United Kingdom	WEL STEL (mg/m <sup>3</sup> )	7 mg/m <sup>3</sup>
Norway	Local name	Carbon Black (lampsot)
Norway	Grenseverdier (AN) (mg/m <sup>3</sup> )	3.5 mg/m <sup>3</sup>

### 8.2. Exposure controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

#### Hand protection:

Protective gloves. (PVC, neoprene, nitrile rubber). Gloves must be replaced after each use and whenever signs of wear or perforation appear

#### Eye protection:

Eye protection should only be necessary where liquid could be splashed or sprayed.

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

No respiratory protection needed under normal use conditions

#### Environmental exposure controls:

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Solid marker containing liquid colored paint.
Colour	: Various.
Odour	: aromatic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: 139 - 141 °C
Flash point	: 30 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: > 1
Relative density	: > 1
Solubility	: No data available
Log Pow	: No data available

# Nissen by Markal Jumbo Feltip Paint Marker: White, Yellow, Black, Red

## Safety Data Sheet

according to Regulation (EU) 2015/830

Viscosity, kinematic	: 50 cSt
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No dangerous reactions known.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

Strong oxidizers.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

**Acute toxicity** : Inhalation:dust,mist: Harmful if inhaled.

ATE CLP (dust,mist)	3 mg/l/4h
---------------------	-----------

<b>Ethylbenzene (100-41-4)</b>	
LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	17.8 ml/kg
LC50 inhalation rat (ppm)	< 1500 ppm

<b>Titanium dioxide (13463-67-7)</b>	
LD50 oral rat	> 5000 mg/kg
LC50 inhalation rat (mg/l)	> 6.82 mg/l/4h

<b>Xylene (1330-20-7)</b>	
LD50 oral rat	4300 mg/kg
LD50 dermal rat	1100 mg/kg
LC50 inhalation rat (ppm)	6247 ppm/4h
LC50 inhalation rat (Dust/Mist - mg/l/4h)	1.5 mg/l/4h
LC50 inhalation rat (Vapours - mg/l/4h)	47635 mg/l/4h

<b>Carbon black (1333-86-4)</b>	
LD50 oral rat	> 8000 mg/kg
LC50 inhalation rat (mg/l)	> 4.6 mg/m <sup>3</sup> 4 h

**Skin corrosion/irritation** : Causes skin irritation.

**Serious eye damage/irritation** : Causes serious eye irritation.

**Respiratory or skin sensitisation** : Not classified

**Germ cell mutagenicity** : Not classified

**Carcinogenicity** : Suspected of causing cancer.

<b>Ethylbenzene (100-41-4)</b>	
IARC group	2B - Possibly carcinogenic to humans

<b>Titanium dioxide (13463-67-7)</b>	
NOAEL (chronic, oral, animal/male, 2 years)	5 mg/kg bodyweight rat
Additional information	Carcinogen. Inhalation of dust

# Nissen by Markal Jumbo Feltip Paint Marker: White, Yellow, Black, Red

## Safety Data Sheet

according to Regulation (EU) 2015/830

### Carbon black (1333-86-4)

IARC group : 2B - Possibly carcinogenic to humans, Inhalation of dust

**Reproductive toxicity** : Not classified

**STOT-single exposure** : May cause respiratory irritation.

**STOT-repeated exposure** : May cause damage to organs through prolonged or repeated exposure.

**Aspiration hazard** : Not classified

### Nissen by Markal Jumbo Feltip Paint Marker: White, Yellow, Black, Red

Viscosity, kinematic : 50 mm<sup>2</sup>/s

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

### Ethylbenzene (100-41-4)

LC50 fish 1 : 5.1 mg/l

EC50 other aquatic organisms 1 : 7.7 mg/l

NOEC (acute) : 3.3 mg/l

### 12.2. Persistence and degradability

#### Ethylbenzene (100-41-4)

Persistence and degradability : Not established.

#### Carbon black (1333-86-4)

Persistence and degradability : Not readily biodegradable.

### 12.3. Bioaccumulative potential

#### Ethylbenzene (100-41-4)

Bioaccumulative potential : Not established.

### 12.4. Mobility in soil

#### Nissen by Markal Jumbo Feltip Paint Marker: White, Yellow, Black, Red

Mobility in soil : Not established

### 12.5. Results of PBT and vPvB assessment

No additional information.

### 12.6. Other adverse effects

No additional information.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Additional information : Flammable vapours may accumulate in the container.

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

### 14.1. UN number

UN-No. (ADR) : 1263

UN-No. (IMDG) : 1263

UN-No. (IATA) : 1263

UN-No. (ADN) : 1263

UN-No. (RID) : 1263

### 14.2. UN proper shipping name

Proper Shipping Name (ADR) : PAINT

Proper Shipping Name (IMDG) : PAINT

Proper Shipping Name (IATA) : PAINT

Proper Shipping Name (ADN) : PAINT

# Nissen by Markal Jumbo Feltip Paint Marker: White, Yellow, Black, Red

## Safety Data Sheet

according to Regulation (EU) 2015/830

Proper Shipping Name (RID) : PAINT  
Transport document description (ADR) : UN 1263 PAINT, 3, III, (D/E)  
Transport document description (IMDG) : UN 1263 PAINT, 3, III  
Transport document description (IATA) : UN 1263 PAINT, 3, III  
Transport document description (ADN) : UN 1263 PAINT, 3, III  
Transport document description (RID) : UN 1263 PAINT, 3, III

### 14.3. Transport hazard class(es)

#### ADR

Transport hazard class(es) (ADR) : 3  
Danger labels (ADR) : 3



#### IMDG

Transport hazard class(es) (IMDG) : 3  
Danger labels (IMDG) : 3



#### IATA

Transport hazard class(es) (IATA) : 3  
Hazard labels (IATA) : 3



#### ADN

Transport hazard class(es) (ADN) : 3  
Danger labels (ADN) : 3



#### RID

Transport hazard class(es) (RID) : 3  
Danger labels (RID) : 3



### 14.4. Packing group

Packing group (ADR) : III

# Nissen by Markal Jumbo Feltip Paint Marker: White, Yellow, Black, Red

## Safety Data Sheet

according to Regulation (EU) 2015/830

Packing group (IMDG) : III  
Packing group (IATA) : III  
Packing group (ADN) : III  
Packing group (RID) : III

### 14.5. Environmental hazards

Dangerous for the environment : No  
Marine pollutant : No  
Other information : No supplementary information available

### 14.6. Special precautions for user

#### - Overland transport

Classification code (ADR) : F1  
Hazard identification number (Kemler No.) : 30  
Orange plates :



Tunnel restriction code (ADR) : D/E  
EAC code : •3YE

#### - Transport by sea

EmS-No. (Fire) : F-E  
EmS-No. (Spillage) : S-E  
Stowage category (IMDG) : A  
Properties and observations (IMDG) : Miscibility with water depends upon the composition.

#### - Air transport

Special provisions (IATA) : A3, A72, A192  
ERG code (IATA) : 3L

#### - Inland waterway transport

Classification code (ADN) : F1

#### - Rail transport

Classification code (RID) : F1

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

3. Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008	Ethylbenzene - Xylene
3(a) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F	Nissen by Markal Jumbo Feltip Paint Marker: White, Yellow, Black, Red - Ethylbenzene - Xylene
3(b) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	Nissen by Markal Jumbo Feltip Paint Marker: White, Yellow, Black, Red - Ethylbenzene - Xylene
40. Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.	Ethylbenzene - Xylene

Contains no substance on the REACH candidate list

# Nissen by Markal Jumbo Feltip Paint Marker: White, Yellow, Black, Red

## Safety Data Sheet

according to Regulation (EU) 2015/830

Contains no REACH Annex XIV substances

### 15.1.2. National regulations

#### Germany

VwVwS Annex reference : Water hazard class (WGK) 3, severe hazard to waters (Classification according to AwSV, Annex 1)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

#### Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed

SZW-lijst van mutagene stoffen : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : Xylene is listed

#### Denmark

Class for fire hazard : Class II-1

Store unit : 5 liter

Classification remarks : R10 <H226;H315;H319;H332;H335;H351;H373>; Emergency management guidelines for the storage of flammable liquids must be followed

Recommendations Danish Regulation : Young people below the age of 18 years are not allowed to use the product  
Pregnant/breastfeeding women working with the product must not be in direct contact with the product  
The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

### 15.2. Chemical safety assessment

No additional information available

## SECTION 16: Other information

Abbreviations and acronyms:

ACGIH (American Conference of Government Industrial Hygienists)
ATE: Acute Toxicity Estimate
CAS (Chemical Abstracts Service) number
CLP: Classification, Labelling, Packaging.
EC50: Environmental Concentration associated with a response by 50% of the test population.
GHS: Globally Harmonized System (of Classification and Labeling of Chemicals).
LD50: Lethal Dose for 50% of the test population
LC50: Median lethal concentration
STEL: Short Term Exposure Limits
TSCA: Toxic Substances Control Act
TWA: Time Weighted Average

Data sources : ACGIH (American Conference of Government Industrial Hygienists).  
Chemical Inspection & Regulation Service; accessed at: [http://www.cirs-reach.com/Inventory/Global\\_Chemical\\_Inventories.html](http://www.cirs-reach.com/Inventory/Global_Chemical_Inventories.html).  
Component Supplier SDSs.  
European Chemicals Agency (ECHA) C&L Inventory database. Accessed at <http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database>.  
European Chemicals Agency (ECHA) Registered Substances list.  
Internal Company test data.  
Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition.  
National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition.  
OSHA 29CFR 1910.1200 Hazard Communication Standard.  
TSCA Chemical Substance Inventory. Accessed at <http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html>.



# Nissen by Markal Jumbo Feltip Paint Marker: White, Yellow, Black, Red

## Safety Data Sheet

according to Regulation (EU) 2015/830

Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Flam. Liq. 3	H226	On basis of test data
Acute Tox. 4 (Inhalation:dust,mist)	H332	Calculation method
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Carc. 2	H351	Calculation method
STOT SE 3	H335	Calculation method
STOT RE 2	H373	Calculation method

**SDS Prepared by:** The Redstone Group, LLC  
6077 Frantz Rd.  
Suite 206  
Dublin, OH USA 43017  
T 614-923-7472  
[www.redstonegrp.com](http://www.redstonegrp.com)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*