

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Product form : Mixture  
Trade name : PRO-LINE® XT Paint Marker Silver

**1.2. Relevant identified uses of the substance or mixture and uses advised against****1.2.1. Relevant identified uses**


Use of the substance/mixture : Paint.

**1.2.2. Uses advised against**

No additional information available

**1.3. Details of the supplier of the safety data sheet**

LA-CO Industries Europe S.A.S.  
Parc Industriel de la Plaine de  
l'Ain - Allée des Combes.  
01150.BLYES.France.  
Phone: +33 (0)4 74 46 23 23  
Fax: +33 (0)4 74 46 23 29  
E-mail: info@eu.laco.com  
Web: http://www.markal.com

**1.4. Emergency telephone number**

Emergency number : 24-hour emergency: CHEMTREC- U.S. : 1-800-424-9300 International: +1-703-527-3887

EU Member State	Officieel adviesorgaan	Adres	Noodnummer
AUSTRIA	Vergiftungsinformationszentrale (Poisons Information Centre)	Allgemeines Krankenhaus Waehringer Geurtel 18-20 1090 Wien	+43 1 406 43 43
BELARUS	The Belarus Republican Poisons Centre	Kizhevatova str. 58 220115 Minsk	+375 (0)17 201 9158
BELGIUM	Centre Anti-Poisons/Antigifocentrum c/o Hôpital Central de la Base - Reine Astrid	Rue Bruyn 1 B -1120 Bruxelles/Brussel	+32 70 245 245
BULGARIA	Национален токсикологичен информационен център National Clinical Toxicology Centre, Emergency Medical Institute "Pirogov"	21 Tottleben Boulevard 1606 SOFIA	+359 2 9154 409
CROATIA	Poisons Control Centre Institute of Medical Research & Occupational Health	Ksaverska Cesta 2 P.O. Box 291 HR-10000 Zagreb	+385 1 234 8342
CZECH REPUBLIC	Toxikologické informační středisko Clinic For Occupational Medicine, 1st Medical Faculty, Charles University	Na Bojišti 1 120 00 Praha 2	+42 2 2491 9293 +42 2 2491 5402
DENMARK	Gifflinjen Bispebjerg Hospital	Bispebjerg Bakke 23, 60, 1 DK-2400 København NV	+45 82 12 12 12 +45 35 31 55 55
ESTONIA	Mürgistusteabekeskus	Gonsiori 29 15027 Tallinn	+372 626 93 90
FINLAND	Myrkytystietokeskus	P.O.B 340 (Haartmaninkatu 4) HUS SF - 00029 Helsinki	+358 9 471 977
FRANCE	ORFILA		+33 1 45 42 59 59
GERMANY	Berliner Betrieb für Zentrale Gesundheitliche Aufgaben	Oranienburger Strasse 285 13437 Berlin	+49 30 19240
GERMANY	Informations und Beratungszentrum für Vergiftungsfälle	Kirrberger Straße, Gebäude 9 D-66421 Homburg/Saar	+49 6841 19240
GERMANY	Beratungstelle bei Vergiftungen, Klinische Toxikologie und Beratungsstelle bei Vergiftungen	Langenbeckstrasse 1 55131 Mainz	+49 6131 19240
GREECE	Poisons Information Centre	11527 Athens	+30 10 779 3777
HUNGARY	Országos Kémiai Biztonsági Intézet (National Institute of Chemical Safety) Egészségügyi Toxikológiai Tájékoztató Szolgálat (Health Toxicological Information Service)	1437 Budapest PO Box 839 1097 Budapest, Nagyvárad tér 2	+36 80 20 11 99
ICELAND	Eitrunarmiðstöðin	Eitrunarmiðstöðin 108 Reykjavik	+354 543 22 22
IRELAND	National Poisons Information Centre	Beaumont Hospital PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2166
LATVIA	Valsts Toksikoloģijas centra Saindēšanās un zāļu informācijas centrs	2 Hipocrate Street LV 1038 Riga	+371 67 04 24 73

# PRO-LINE® XT Paint Marker Silver

## Safety Data Sheet

according to Regulation (EU) 2015/830

LITHUANIA	Apsinuodijimų kontrolės ir informacijos biuras	Siltnamiu 29 2043 Vilnius	+370 5 236 20 52/+370 687 53 378
MALTA	Medicines & Poisons Info Office	Mater Dei Hospital, Msida MSD 2090 Malta	25450000
NETHERLANDS	Nationaal Vergiftigingen Informatie Centrum National Institute for Public Health and the Environment, NB this service is only available to health professionals	Huispostnummer B.00.118, PO Box 85500 3508 GA Utrecht	+31 30 274 88 88
PORTUGAL	Centro de Informação Antivenenos Instituto Nacional de Emergência Médica (INEM)	Rua Almirante Barroso, 36 1000-013 Lisboa	808 250 143 (for use only in Portugal), +351 21 330 3284
ROMANIA	Biroul pentru Regulamentul Sanitar International si Informare Toxicologica	Str. Dr. Leonte Anastasievici Nr.1-3, Sector 5 50463 Bucuresti	+40 21 318 36 06
SLOVAKIA	Národné toxikologické informačné centrum University Hospital Bratislava	Limbová 5 833 05 Bratislava	+421 2 54 77 4 166
SPAIN	Servicio de Información Toxicológica Instituto Nacional de Toxicología, Departamento de Madrid	Calle Luis Cabrera 9 E-28002 Madrid	+34 91 562 04 20
SWEDEN	Giftinformationscentralen Swedish Poisons Information Centre, Karolinska Hospital	Box 60 500 SE-171 76 Stockholm	+46 8 33 12 31 (International) 112 (National)
SWITZERLAND	Centre Suisse d'Information Toxicologique	Freiestrasse 16 Postfach CH-8028 Zurich	+41 44 251 51 51 (International) 145 (National)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 3 H226

Skin Sens. 1 H317

Repr. 2 H361

STOT RE 1 H372

Full text of classification categories and H statements : see section 16

#### Adverse physicochemical, human health and environmental effects

No additional information available

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

GHS08

Signal word (CLP) :

Danger

Hazardous ingredients :

cobalt bis(2-ethylhexanoate)

Hazard statements (CLP) :

H226 - Flammable liquid and vapour  
H317 - May cause an allergic skin reaction  
H361 - Suspected of damaging fertility or the unborn child  
H372 - Causes damage to organs through prolonged or repeated exposure

Precautionary statements (CLP) :

P201 - Obtain special instructions before use  
P202 - Do not handle until all safety precautions have been read and understood  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
P233 - Keep container tightly closed  
P240 - Ground/bond container and receiving equipment  
P241 - Use explosion-proof electrical, lighting equipment  
P260 - Do not breathe mist, vapours  
P264 - Wash hands thoroughly after handling  
P270 - Do not eat, drink or smoke when using this product  
P272 - Contaminated work clothing should not be allowed out of the workplace  
P280 - Wear eye protection, protective gloves  
P302+P352 - IF ON SKIN: Wash with plenty of water  
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
P314 - Get medical advice/attention if you feel unwell  
P321 - Specific treatment (see First aid measures on this label)  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention  
P362+P364 - Take off contaminated clothing and wash it before reuse

# PRO-LINE® XT Paint Marker Silver

## Safety Data Sheet

according to Regulation (EU) 2015/830

P370+P378 - In case of fire: Use Suitable extinguishing media to extinguish  
P403+P235 - Store in a well-ventilated place. Keep cool  
P405 - Store locked up  
P501 - Dispose of contents/container to an authorised waste collection point

EUH-statements

: EUH066 - Repeated exposure may cause skin dryness or cracking

### 2.3. Other hazards

PBT: not yet assessed

vPvB: not yet assessed

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Comments

: Only component with health hazards above the applicable thresholds and/or Exposure Limit values are shown.

Exact concentrations are withheld as trade secret.

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Cyclohexanone	(CAS No) 108-94-1 (EC no) 203-631-1 (EC index no) 606-010-00-7	20 – 30	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation:dust,mist), H332
tert-butyl acetate	(CAS No) 540-88-5 (EC no) 208-760-7 (EC index no) 607-026-00-7	20 – 30	Flam. Liq. 2, H225
aluminium powder (stabilised)	(CAS No) 7429-90-5 (EC no) 231-072-3 (EC index no) 013-001-00-1	10 – 20	Flam. Sol. 1, H228 Water-react. 2, H261
Naphtha (petroleum), hydrotreated heavy (benzene < 0.1%)	(CAS No) 64742-48-9 (EC no) 265-150-3 (EC index no) 649-327-00-6	10 – 20	Asp. Tox. 1, H304
Stoddard solvent (benzene < 0.1%)	(CAS No) 8052-41-3 (EC no) 232-489-3 (EC index no) 649-345-00-4	1 – 5	Flam. Liq. 3, H226 STOT RE 1, H372 Asp. Tox. 1, H304
Ethyl acetate	(CAS No) 141-78-6 (EC no) 205-500-4 (EC index no) 607-022-00-5	1 – 5	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
2-ethylhexanoic acid, zirconium salt	(CAS No) 22464-99-9 (EC no) 245-018-1	0.1 – 1	Repr. 2, H361fd
Distillates (petroleum), hydrotreated light	(CAS No) 64742-47-8 (EC no) 265-149-8 (EC index no) 649-422-00-2	0.1 – 1	Asp. Tox. 1, H304
2-ethylhexanoic acid, manganese salt	(CAS No) 15956-58-8 (EC no) 240-085-3	0.1 – 1	Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319 Repr. 2, H361d STOT RE 2, H373 Aquatic Chronic 2, H411
2-methylpropan-2-ol	(CAS No) 75-65-0 (EC no) 200-889-7 (EC index no) 603-005-00-1	0 – 1	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation:dust,mist), H332 Eye Irrit. 2, H319 STOT SE 3, H335
cobalt bis(2-ethylhexanoate)	(CAS No) 136-52-7 (EC no) 205-250-6	0.1 – 1	Eye Irrit. 2, H319 Skin Sens. 1A, H317 Repr. 2, H361 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of R- and H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general

: Get medical advice/attention if you feel unwell.

First-aid measures after inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

First-aid measures after skin contact

: Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. Repeated exposure may cause skin dryness or cracking.

First-aid measures after eye contact

: In case of contact, immediately flush eyes with plenty of water.

First-aid measures after ingestion

: Rinse mouth. Do NOT induce vomiting.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries

: Suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure.

# PRO-LINE® XT Paint Marker Silver

## Safety Data Sheet

according to Regulation (EU) 2015/830

Symptoms/injuries after skin contact : May cause an allergic skin reaction.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

Unsuitable extinguishing media : None known.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapour.

Explosion hazard : May form flammable/explosive vapour-air mixture.

Hazardous decomposition products in case of fire : Carbon oxides (CO, CO<sub>2</sub>), metallic oxides.

### 5.3. Advice for firefighters

Firefighting instructions : Eliminate all ignition sources if safe to do so. Exercise caution when fighting any chemical fire.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Use self-contained breathing apparatus. EN469.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking. Avoid all eye and skin contact and do not breathe vapour and mist.

#### 6.1.1. For non-emergency personnel

Protective equipment : Wear suitable gloves.

Emergency procedures : Evacuate unnecessary personnel.

#### 6.1.2. For emergency responders

Protective equipment : Wear suitable gloves.

Emergency procedures : Stop leak if safe to do so. Ventilate area.

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Wipe up with absorbent material (for example cloth).

### 6.4. Reference to other sections

Section 13: disposal information. Section 7: safe handling.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapours are flammable.

Precautions for safe handling : No open flames. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist, vapours.

Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting equipment.

Storage conditions : Keep container closed when not in use.

Incompatible products : Oxidizing agent. Acids. Alkali. Moisture.

Incompatible materials : Heat sources.

Heat and ignition sources : Keep away from heat, sparks and flame.

Prohibitions on mixed storage : Incompatible materials.

Storage area : Store in dry, cool, well-ventilated area.

### 7.3. Specific end use(s)

Marking.

# PRO-LINE® XT Paint Marker Silver

## Safety Data Sheet

according to Regulation (EU) 2015/830

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

aluminium powder (stabilised) (7429-90-5)		
Belgium	Limit value (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup>
Belgium	Remark (BE)	(Aluminium, métal et composés insolubles, fraction alvéolaire)
Denmark	Grænseværdie (kortvarig) (mg/m <sup>3</sup> )	4 mg/m <sup>3</sup> (respirabel) 10 mg/m <sup>3</sup> (total)
Finland	HTP-arvo (8h) (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
Finland	Huomautus (FI)	(Alumiini, liukoiset yhdisteet)
France	VME (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (pulvérulent) 10 mg/m <sup>3</sup> (metal)
Germany	TRGS 903 (BGW)	200 µg/l
Germany	Remark (TRGS 903)	Aluminium (Urin; Expositionsende bzw. Schichtende)
Hungary	Megjegyzések (HU)	(respirábilis por)
Ireland	OEL (8 hours ref) (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup>
Ireland	Notes (IE)	(respirable dust)
Lithuania	IPRV (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup> (alveoline frakcija) 1 mg/m <sup>3</sup> (Aliuminis (metalas) ir jo tirpus junginiai, kaip Al) 5 mg/m <sup>3</sup> (ákvepiamoji frakcija )
Netherlands	Grenswaarde TGG 8H (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Poland	NDS (mg/m <sup>3</sup> )	2.5 mg/m <sup>3</sup> (dymy, pyl calkowity) 1.2 mg/m <sup>3</sup> (dymy, pyl respirabilny)
Slovakia	NPHV (priemerná) (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
Slovakia	NPHV (priemerná) (ppm)	60 µg/g creatinine (Hlinik, M,a) 25 µg/g creatinine (Celkový, M,,d) 150 µg/g creatinine (Celkový,M,b)
Spain	VLA-ED (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (inhalable aerosol) 5 mg/m <sup>3</sup> (respirable aerosol)
Sweden	nivågränsvärde (NVG) (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup> (Aluminium, lösliga föreningar, som Al) 5 mg/m <sup>3</sup> (totaldamm, som Al) 2 mg/m <sup>3</sup> (respirabelt damm, som Al)
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (inhalable dust) 4 mg/m <sup>3</sup> (respirable dust)
Norway	Merknader (NO)	(Aluminiumpulver, pyroteknikk)
Switzerland	VME (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup>
Switzerland	Remark (CH)	(alveolengängiger Staub)
Naphtha (petroleum), hydrotreated heavy (benzene < 0.1%) (64742-48-9)		
Cyclohexanone (108-94-1)		
Denmark	Grænseværdie (kortvarig) (mg/m <sup>3</sup> )	80 mg/m <sup>3</sup>
Denmark	Grænseværdie (kortvarig) (ppm)	20 ppm
Finland	Huomautus (FI)	iho
Slovakia	NPHV (priemerná) (mg/m <sup>3</sup> )	40.8 mg/m <sup>3</sup>
Slovakia	NPHV (priemerná) (ppm)	10 ppm
Slovakia	Upozornenie (SK)	poznámka K
Spain	VLA-ED (mg/m <sup>3</sup> )	41 mg/m <sup>3</sup> vía dérmica,VLI,VLB
Spain	VLA-ED (ppm)	10 ppm vía dérmica,VLI,VLB 80 ppm I,S Con hidrólisis (9) "(1,2- Ciclohexanodiol en orina; Final de la semana laboral 1)" 8 ppm I,S Con hidrólisis (9) "(1,2- Ciclohexanodiol en orina; Final de la jornada laboral 2)"
Spain	VLA-EC (mg/m <sup>3</sup> )	82 mg/m <sup>3</sup> vía dérmica,VLI,VLB
Spain	VLA-EC (ppm)	20 ppm vía dérmica,VLI,VLB
Ethyl acetate (141-78-6)		
Denmark	Grænseværdie (kortvarig) (mg/m <sup>3</sup> )	1080 mg/m <sup>3</sup>
Denmark	Grænseværdie (kortvarig) (ppm)	300 ppm

# PRO-LINE® XT Paint Marker Silver

## Safety Data Sheet

according to Regulation (EU) 2015/830

<b>Ethyl acetate (141-78-6)</b>		
Slovakia	NPHV (priemerná) (mg/m <sup>3</sup> )	500 mg/m <sup>3</sup>
Slovakia	NPHV (priemerná) (ppm)	150 ppm
Spain	VLA-ED (mg/m <sup>3</sup> )	1460 mg/m <sup>3</sup>
Spain	VLA-ED (ppm)	400 ppm
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	730 mg/m <sup>3</sup>
United Kingdom	WEL STEL (mg/m <sup>3</sup> )	1460 mg/m <sup>3</sup>
<b>2-methylpropan-2-ol (75-65-0)</b>		
Finland	Huomautus (FI)	iho
Germany	TRGS 900 Limitation of exposure peaks (mg/m <sup>3</sup> )	248 mg/m <sup>3</sup>
Germany	TRGS 900 Limitation of exposure peaks (ppm)	80 ppm
Slovakia	NPHV (priemerná) (mg/m <sup>3</sup> )	62 mg/m <sup>3</sup>
Slovakia	NPHV (priemerná) (ppm)	20 ppm
Spain	VLA-ED (mg/m <sup>3</sup> )	308 mg/m <sup>3</sup>
Spain	VLA-ED (ppm)	100 ppm
Spain	VLA-EC (mg/m <sup>3</sup> )	462 mg/m <sup>3</sup>
Spain	VLA-EC (ppm)	150 ppm
Spain	Notes	s
Sweden	Anmärkning (SE)	H
Norway	Grenseverdier (Takverdi) (mg/m <sup>3</sup> )	75 mg/m <sup>3</sup>
Norway	Grenseverdier (Takverdi) (ppm)	25 ppm
<b>Distillates (petroleum), hydrotreated light (64742-47-8)</b>		
Germany	TRGS 900 Occupational exposure limit value (mg/m <sup>3</sup> )	600 mg/m <sup>3</sup>
<b>Stoddard solvent (benzene &lt; 0.1%) (8052-41-3)</b>		
Denmark	Grænseværdie (kortvarig) (mg/m <sup>3</sup> )	290 mg/m <sup>3</sup>
Denmark	Grænseværdie (kortvarig) (ppm)	50 ppm
Denmark	Anmærkninger (DK)	(Terpentin, mineralsk, max. 20 pct. aromater; 2)

### 8.2. Exposure controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Personal protective equipment	: Avoid all unnecessary exposure.
Hand protection	: Use rubber gloves. EN374.
Eye protection	: None under normal use.
Respiratory protection	: None under normal use.
Consumer exposure controls	: Keep out of reach of children.
Other information	: Do not eat, drink or smoke when using this product.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Solid marker containing liquid colored paint.
Colour	: Silver.
Odour	: Solvent.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 23 - 37.8 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Flammable liquid and vapour
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available

# PRO-LINE® XT Paint Marker Silver

## Safety Data Sheet

according to Regulation (EU) 2015/830

Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: 25 cSt @ 40 °C
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

VOC content : 67 %

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No dangerous reactions known.

### 10.2. Chemical stability

Flammable liquid and vapour. May form flammable/explosive vapour-air mixture.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Open flame. Overheating. Direct sunlight. Heat. Sparks.

### 10.5. Incompatible materials

Oxidizer. Acids. Alkali. Moisture.

### 10.6. Hazardous decomposition products

May release flammable gases. Thermal decomposition generates : metallic oxides. Carbon oxides (CO, CO<sub>2</sub>).

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

aluminium powder (stabilised) (7429-90-5)	
LD50 oral rat	> 15900 mg/kg
LC50 inhalation rat (mg/l)	> 2.3 mg/l/4h No mortality observed in this study.
Naphtha (petroleum), hydrotreated heavy (benzene < 0.1%) (64742-48-9)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 5610 mg/m <sup>3</sup>
Cyclohexanone (108-94-1)	
ATE CLP (dust,mist)	1.500 mg/l/4h
Ethyl acetate (141-78-6)	
LD50 oral rat	5620 mg/kg
LD50 dermal rabbit	> 20000 mg/kg
LC50 inhalation rat (mg/l)	> 18 mg/l/4h
ATE CLP (oral)	5620.000 mg/kg bodyweight
tert-butyl acetate (540-88-5)	
LD50 oral rat	4100 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (ppm)	4211 ppm 6 h
ATE CLP (oral)	4100.000 mg/kg bodyweight
2-methylpropan-2-ol (75-65-0)	
LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (ppm)	> 9700 ppm/4h
ATE CLP (oral)	3500.000 mg/kg bodyweight
ATE CLP (dust,mist)	1.500 mg/l/4h
2-ethylhexanoic acid, manganese salt (15956-58-8)	
LD50 oral rat	1470 mg/kg bodyweight read-across MnCl <sub>2</sub>
ATE CLP (oral)	1470.000 mg/kg bodyweight

# PRO-LINE® XT Paint Marker Silver

## Safety Data Sheet

according to Regulation (EU) 2015/830

<b>Distillates (petroleum), hydrotreated light (64742-47-8)</b>	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (Dust/Mist - mg/l/4h)	> 5.28 mg/l/4h

<b>Stoddard solvent (benzene &lt; 0.1%) (8052-41-3)</b>	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 10 mg/l/4h

<b>cobalt bis(2-ethylhexanoate) (136-52-7)</b>	
LD50 oral rat	3129 (1750 - 5000) mg/l
LD50 dermal rat	> 2000 mg/kg

<b>2-ethylhexanoic acid, zirconium salt (22464-99-9)</b>	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 4.3 mg/l/4h

<b>Skin corrosion/irritation</b>	: Not classified Repeated exposure may cause skin dryness or cracking
<b>Serious eye damage/irritation</b>	: Not classified
<b>Respiratory or skin sensitisation</b>	: May cause an allergic skin reaction.
<b>Germ cell mutagenicity</b>	: Not classified
<b>Carcinogenicity</b>	: Not classified
<b>Reproductive toxicity</b>	: Suspected of damaging fertility or the unborn child.
<b>Specific target organ toxicity (single exposure)</b>	: Not classified
<b>Specific target organ toxicity (repeated exposure)</b>	: Causes damage to organs through prolonged or repeated exposure.

<b>2-ethylhexanoic acid, zirconium salt (22464-99-9)</b>	
NOAEL (oral, rat, 90 days)	300 mg/kg bodyweight/day read across 2-ethylhexanoic acid; P-generation

**Aspiration hazard** : Not classified

## SECTION 12: Ecological information

### 12.1. Toxicity

<b>aluminium powder (stabilised) (7429-90-5)</b>	
LC50 fish 1	> 218.64 mg/l ASTM 2000; test material: aluminium chloride hexahydrate; Pimephales promelas
EC50 Daphnia 1	1.4 mg/l OECD Guideline 202; test material: Aluminium hydroxide
LOEC (acute)	72.89 mg/l
NOEC (acute)	37.2 mg/l

<b>Naphtha (petroleum), hydrotreated heavy (benzene &lt; 0.1%) (64742-48-9)</b>	
LC50 fish 1	8.2 mg/l

<b>Ethyl acetate (141-78-6)</b>	
LC50 fish 1	220 mg/l
EC50 Daphnia 1	1200 mg/l
NOEC chronic fish	< 9.35 mg/l

<b>tert-butyl acetate (540-88-5)</b>	
LC50 fish 1	240 mg/l 96 h
EC50 Daphnia 1	410 mg/l 24 h

<b>2-methylpropan-2-ol (75-65-0)</b>	
LC50 fish 1	> 961 mg/l 96 h
EC50 Daphnia 1	933 mg/l 48 h

<b>cobalt bis(2-ethylhexanoate) (136-52-7)</b>	
LC50 fish 1	275 mg/l 96 h
EC50 Daphnia 1	0.441 mg/l 48 h
LOEC (chronic)	0.43 mg/l 34 days read-across cobalt dichloride
NOEC (chronic)	0.21 mg/l 34 days read-across cobalt dichloride

<b>2-ethylhexanoic acid, zirconium salt (22464-99-9)</b>	
LC50 fish 1	> 100 mg/l 96 h



# PRO-LINE® XT Paint Marker Silver

## Safety Data Sheet

according to Regulation (EU) 2015/830

### 2-ethylhexanoic acid, zirconium salt (22464-99-9)

EC50 Daphnia 1	> 0.17 mg/l 48 h
----------------	------------------

#### 12.2. Persistence and degradability

##### Ethyl acetate (141-78-6)

Persistence and degradability	Readily biodegradable.
-------------------------------	------------------------

##### tert-butyl acetate (540-88-5)

Persistence and degradability	Readily biodegradable.
-------------------------------	------------------------

Biodegradation	50 % 28 d
----------------	-----------

##### 2-methylpropan-2-ol (75-65-0)

Persistence and degradability	inherently biodegradable.
-------------------------------	---------------------------

Biodegradation	66 % 56 d
----------------	-----------

##### cobalt bis(2-ethylhexanoate) (136-52-7)

Persistence and degradability	Readily biodegradable.
-------------------------------	------------------------

#### 12.3. Bioaccumulative potential

##### Ethyl acetate (141-78-6)

Bioaccumulative potential	Not expected to bioaccumulate.
---------------------------	--------------------------------

##### tert-butyl acetate (540-88-5)

BCF fish 1	5.61
------------	------

Log Pow	1.64
---------	------

##### 2-methylpropan-2-ol (75-65-0)

Log Pow	0.317
---------	-------

##### Distillates (petroleum), hydrotreated light (64742-47-8)

Log Kow	2.1 - 5
---------	---------

Bioaccumulative potential	Bioaccumulative potential.
---------------------------	----------------------------

##### Stoddard solvent (benzene < 0.1%) (8052-41-3)

Log Pow	3.16 - 7.15
---------	-------------

##### cobalt bis(2-ethylhexanoate) (136-52-7)

BCF fish 1	2300 (2300 - 3900)
------------	--------------------

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Results of PBT and vPvB assessment

##### PRO-LINE® XT Paint Marker Silver

PBT: not yet assessed
-----------------------

vPvB: not yet assessed
------------------------

##### Component

Ethyl acetate (141-78-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
--------------------------	---

#### 12.6. Other adverse effects

No additional information available

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Sewage disposal recommendations	: Do not dispose of waste into sewer.
Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
Additional information	: Handle empty containers with care because residual vapours are flammable.
European List of Waste (LoW) code	: For disposal within the EC, the appropriate code according to the European Waste Catalogue (EWC) should be used.
H code	: H10 - 'Toxic for reproduction': substances and preparations which, if they are inhaled or ingested or if they penetrate the skin, may induce non-hereditary congenital malformations or increase their incidence. H13 - 'Sensitizing': substances and preparations which, if they are inhaled or if they penetrate the skin, are capable of eliciting a reaction of hypersensitization such that on further exposure to the substance or preparation, characteristic adverse effects are produced. H3-B - 'Flammable': liquid substances and preparations having a flash point equal to or greater than 21 °C and less than or equal to 55 °C. H5 - 'Harmful': substances and preparations which, if they are inhaled or ingested or if they penetrate the skin, may involve limited health risks.

# PRO-LINE® XT Paint Marker Silver

## Safety Data Sheet

according to Regulation (EU) 2015/830

### SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

#### 14.1. UN number

UN-No. (ADR) : 1263  
UN-No. (IATA) : 1263  
UN-No. (IMDG) : 1263  
UN-No. (ADN) : 1263

#### 14.2. UN proper shipping name

Proper Shipping Name (ADR) : Paint  
Proper Shipping Name (IATA) : Paint  
Proper Shipping Name (IMDG) : PAINT  
Proper Shipping Name (ADN) : PAINT  
Transport document description (ADR) : UN 1263 PAINT, 3, III, (D/E)

#### 14.3. Transport hazard class(es)

Class (ADR) : 3  
Classification code (ADR) : F1  
Class (IATA) : 3  
Class (IMDG) : 3  
Class (ADN) : 3  
Classification code (ADN) : F1

#### 14.4. Packing group

Packing group (ADR) : III  
Packing group (IATA) : III  
Packing group (IMDG) : III  
Packing group (ADN) : III

#### 14.5. Environmental hazards

Other information : No supplementary information available.

#### 14.6. Special precautions for user

##### 14.6.1. Overland transport

Hazard identification number (Kemler No.) : 30  
Classification code (ADR) : F1  
Orange plates :



Tunnel restriction code (ADR) : D/E  
EAC code : •3YE

##### 14.6.2. Transport by sea

EmS-No. (Fire) : F-E  
EmS-No. (Spillage) : S-E  
Stowage category (IMDG) : A

##### 14.6.3. Inland waterway transport

Carriage prohibited (ADN) : No

#### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions  
Contains no substance on the REACH candidate list  
Contains no REACH Annex XIV substances  
VOC content : 67 %

# PRO-LINE® XT Paint Marker Silver

## Safety Data Sheet

according to Regulation (EU) 2015/830

### 15.1.2. National regulations

#### Germany

Water hazard class (WGK) : 2 - hazard to waters  
WGK remark : Classification based on the components in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS)

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

according to Regulation (EU) 2015/830

Indication of changes:

Original Document.

Abbreviations and acronyms:

	ATE: Acute Toxicity Estimate
	CAS (Chemical Abstracts Service) number
	CLP: Classification, Labelling, Packaging.
	EC50: Environmental Concentration associated with a response by 50% of the test population.
	GHS: Globally Harmonized System (of Classification and Labeling of Chemicals).
	LD50: Lethal Dose for 50% of the test population
	OSHA: Occupational Safety & Health Administration
	PBT: Persistent, Bioaccumulative, Toxic
	TWA: Time Weighted Average
	TSCA: Toxic Substances Control Act

Data sources

: ESIS (European chemical Substances Information System; accessed at: <http://esis.jrc.ec.europa.eu/index.php?PGM=cla>.  
European Chemicals Agency (ECHA) C&L Inventory database. Accessed at <http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database>.  
Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition.  
National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition.  
REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information

: None.

Full text of R-, H- and EUH-statements:

Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Flam. Sol. 1	Flammable solids, Category 1
Repr. 2	Reproductive toxicity, Category 2
Repr. 2	Reproductive toxicity, Category 2
Repr. 2	Reproductive toxicity, Category 2
Skin Sens. 1	Sensitisation — Skin, category 1
Skin Sens. 1A	Sensitisation — Skin, category 1A
STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
Water-react. 2	Substances and Mixtures which, in contact with water, emit flammable gases, Category 2
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour

# PRO-LINE® XT Paint Marker Silver

## Safety Data Sheet

according to Regulation (EU) 2015/830

H228	Flammable solid
H261	In contact with water releases flammable gases
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child
H361d	Suspected of damaging the unborn child
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child
H372	Causes damage to organs through prolonged or repeated exposure
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects
EUH066	Repeated exposure may cause skin dryness or cracking
R10	Flammable
R11	Highly flammable
R15	Contact with water liberates extremely flammable gases
R20	Harmful by inhalation
R22	Harmful if swallowed
R36	Irritating to eyes
R36/37	Irritating to eyes and respiratory system
R43	May cause sensitisation by skin contact
R45	May cause cancer
R46	May cause heritable genetic damage
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R62	Possible risk of impaired fertility
R63	Possible risk of harm to the unborn child
R65	Harmful: may cause lung damage if swallowed
R66	Repeated exposure may cause skin dryness or cracking
R67	Vapours may cause drowsiness and dizziness
F	Highly flammable
N	Dangerous for the environment
Xi	Irritant
Xn	Harmful

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Flam. Liq. 3	H226	On basis of test data
Skin Sens. 1	H317	Calculation method
Repr. 2	H361	Expert judgment
STOT RE 1	H372	Expert judgment

LA-CO EU CLP SDS

**SDS Prepared by:** The Redstone Group, LLC  
6077 Frantz Rd.  
Suite 206  
Dublin, OH USA 43016  
T 614-923-7472  
[www.redstonegrp.com](http://www.redstonegrp.com)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*